



product overview


| | | |
|---|--|---|
| Black annealed wire | Hot galvanized wire | Hot galvanized wire |
|  |  |  |
| Galvanized thatching wire - smooth and ribbed | Green painted gardener wire | bonsai wire |
|  |  |  |
| Blank wire | | Copper-plated wire |
|  | |  |


| Black annealed wire | |
|----------------------------|---|
| Specification mm. | Often used for concrete reinforcement, as packaging wire and as wire for hanging different subjects in the electroplating industry. Being soft and smooth, it is especially suited for processing by hand. |
| Dimensions | 1,0 mm - 6,0 mm. |
| Delivery | In coils of different sizes: 500, 600, 800, and 1.000 kg. In rings of 25 kg. Bremer rings for bailing purposes in sizes of 20 kg and 40 kg. In lengths from 100 mm – 6.000 mm. Ø3,05 mm, however also up to 9.000 mm. |





| Hot galvanized wire | |
|----------------------------|--|
| Specifikationer mm. | Often used as fence wire, bailing wire and handle wire. Since the wire has often been processed, you can use it for a wide variety of subjects - for instance as shelf support and flower hangers. |
| Dimensioner | Ø0,89 mm – Ø10,0 mm. |
| Levering | In coils of ca. 600 – 1.000 kg. In rings of ca. 25 kg. In cut lengths from 15 mm to 6.000 mm. |





| Hot galvanized wire, bright drawn | | |
|--|---|--|
| Specification mm. | Used wherever you need a fine, blank surface. Often used for furniture and office inventory. |  |
| Dimensions | Ø3,0 mm – Ø6,0 mm. | |
| Delivery | In coils of ca. 600-1.000 kg. In rings of ca. 25 kg. In cut lengths from 15 mm to 6.000 mm. | |


| Galvanized thatching wire - smooth and ribbed | | |
|--|--|---|
| Specification mm. | Mainly used for thatching since it is very hard. |  |
| Dimensions | Glat: Ø3,0 mm. – Ø5,0 mm. Ribbet: Ø6,0 mm. | |
| Delivery | Smooth thatching wire in whole coils of ca. 500 kg Smooth thatching wire in cut lengths from 30 mm to 6.000 mm. As thatching wire, we deliver the wire in lengths of 3.000 mm to 6.000 mm and in bundles of ca. 25kg/500 kg. | |

| Chicken wire | | |
|---------------------|----------------------------------|--|
| Specification mm | Galvanized wire for thatching. |  |
| Thickness | Ø0,90 mm – Ø1,0 mm. | |
| Size | 40 and 50 mm (1,5 and 2 inches). | |
| Width | Varies. | |
| Delivery | In rolls of ca. 30 m. | |

| Green painted gardener wire | | |
|------------------------------------|---|---|
| Specification mm. | Mainly used in the gardening industry. |  |
| Dimensions | Ø1,5mm, Ø1,65 mm og Ø2,0 mm. | |
| Delivery | In cut lengths from ca. 300 mm to 2.000 mm. In bundles of 5–10 kg. | |

| Bonzai wire | | |
|--------------------|--|--|
| Specification mm. | Bonzaitråd bruges hovedsageligt til gartnerindustrien. |  |
| Dimensions | | |
| Delivery | | |

| Blank wire | | |
|-----------------------------------|---|--|
| Specification mm. | Used for a wide variety of purposes, for instance in the furniture and plastic industries. It is especially suited for welding, chromium-plating and other forms of surface treatments. |  |
| Dimensions | Ø2,0 mm. – Ø12,0 | |
| Cut lengths: Thin dimensions: | From 15 mm to 6.000 mm. | |
| Cut lengths: Thick dimensions: | From 100 mm to 6.000 mm. | |
| Delivery | In 25 kg and 40 kg. In manufacturing rings of ca. 100/250 kg. In coils of 500, 600, 800 and 1.000 kg. | |

| Copper-plated wire | | |
|---------------------------|---|--|
| Specification mm. | Used for hooks in the painting industry, for lampshades and for hanging different types of signs. Being quite hard, the wire has a great carrying capacity. |  |
| Dimensions | Ø1,5 – Ø4,0 mm. | |
| Delivery | Manufacturing rings in the sizes of ca. 100 kg. In cut lengths from 15 mm – 6.000 mm. | |